



December 2007 **PRELIMINARY**

MM20F020KC


200V 20A FRED
RoHS Compliant

PRODUCT FEATURES

- Ultrafast Recovery Time
- Soft Recovery Characteristics
- Low Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current


APPLICATIONS

- Freewheeling, Snubber, Clamp
- Inversion Welder
- PFC
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- UPS



DESCRIPTION

FRED from MacMic utilizes advanced processing techniques to achieve ultrafast recovery times and higher forward current. Its soft recovery characteristics and high reliability suit for wide industrial applications.



ABSOLUTE MAXIMUM RATINGS

$T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Max.	Unit
V_{RRM}	Repetitive Reverse Voltage		200	V
$I_{F(AV)}$	Average Forward Current	$T_C=100^{\circ}\text{C}$, Per Diode	10	A
		$T_C=100^{\circ}\text{C}$, Per Package	20	A
$I_{F(RMS)}$	RMS Forward Current	$T_C=100^{\circ}\text{C}$, Per Diode	14	A
		$T_C=100^{\circ}\text{C}$, Per Package	28	A
I_{FSM}	Non-Repetitive Surge Forward Current	$t=10\text{ms}$, Sine	100	A
T_J	Junction Temperature		-55 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range		-55 to +150	$^{\circ}\text{C}$

ELECTRICAL AND THERMAL CHARACTERISTICS

$T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Reverse Leakage Current	$V_R=200\text{V}$, $T_J=25^{\circ}\text{C}$	--	--	10	μA
		$V_R=200\text{V}$, $T_J=125^{\circ}\text{C}$	--	--	200	μA
V_F	Forward Voltage	$I_F=10\text{A}$, $T_J=25^{\circ}\text{C}$	--	0.9	1.1	V
		$I_F=10\text{A}$, $T_J=125^{\circ}\text{C}$	--	0.86	--	V
t_{rr}	Reverse Recovery Time ($I_F=1\text{A}$, $V_R=30\text{V}$, $di_F/dt=-200\text{A}/\mu\text{s}$)		--	22	--	ns
t_{rr}	Reverse Recovery Time	$I_F=10\text{A}$	$T_J=25^{\circ}\text{C}$	30	--	ns
t_{rr}	Reverse Recovery Time	$V_R=100\text{V}$		45	--	ns
I_{RRM}	Max. Reverse Recovery Current	$di_F/dt=-200\text{A}/\mu\text{s}$		6	--	A
$R_{\theta JC}$	Thermal Resistance	Junction-to-Case	--	--	3.0	$^{\circ}\text{C}/\text{W}$

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R. of China
Tel.: +86-519-85163708 Fax: +86-519-85162291 Post Code: 213022 Website: www.macmicst.com